

## Stainless Steel IBC Tank (Returnable)

不锈钢 IBC 罐式托盘箱

MODEL NO.: DPLT-50D



### SPECIFICATIONS & SPECIAL

技术规格及特点

#### FEATURES

- |  |                              |
|--|------------------------------|
| 1. Material: SUS304/SUS316L  | 1. 材质: SUS304/SUS316L        |
| 2. External Dimensions: 1,140×1,140×1,475mm  | 2. 箱外尺寸: 1,140×1,140×1,475mm |
| 3. Maximum Payload: 1,615KG  | 3. 最大载重: 1,615KG             |
| 4. Surface treatment: 2B (JIS)   | 4. 外表面处理: 2B (JIS)           |
| 5. Special for carrying/storing/transporting liquid of chemical, pharmaceutical, foodstuff, etc. | 5. 适于化学品、食品等液体的包装、储藏和运输。     |

## Stainless Steel Normal Pressure IBC (Returnable)

不锈钢筒式托盘箱

MODEL NO.: DPLT-50J



### SPECIFICATIONS & SPECIAL

技术规格及特点

#### FEATURES

- |  |                              |
|--|------------------------------|
| 1. Material: SUS304/SUS316L  | 1. 材质: SUS304/SUS316L        |
| 2. External Dimensions: 1,135×1,135×1,510mm                                  | 2. 箱外尺寸: 1,135×1,135×1,510mm |
| 3. Maximum Payload: 2,200KG  | 3. 最大载重: 2,200KG             |
| 4. Surface treatment: 2B (JIS)   | 4. 外表面处理: 2B (JIS)           |
| 5. Special for carrying/storing/transporting hazardous goods of II/III grade | 5. 适于 II、III 类危险品的包装、储存和运输。  |

## TK2 Tank Pallet (Type C) 350 gallon (Returnable)

TK2 装运 UN 危险品货物方型罐式托盘

MODEL NO.: DPLT-116A



### SPECIFICATIONS & SPECIAL

### 技术规格及特点

#### FEATURES

- |  |                              |
|--|------------------------------|
| 1. Material: BODY- SUS304  | 1. 材料: 筒体- SUS304            |
| 2. External Dimensions: 1,150×1,150×1,355mm                      | 2. 箱外尺寸: 1,257×1,105×1,264mm |
| 3. Inside Cubic Capacity: 1.325 CU.M                             | 3. 容积: 1.325 CU.M            |
| 4. Surface treatment: 2B (JIS); welding line with acid Treatment | 4. 外表面处理: 2B (JIS) 焊缝处酸洗     |
| 5. Approvals: UN31AY   | 5. 通过 UN 认证                  |
| 6. Storing and transportation for group II、III dangerous goods.  | 6. 适于包装和运输 II、III类危险品。       |

## Stainless Steel IBC Tank (Returnable)

不锈钢筒式托盘箱

MODEL NO.: DPLT-150



### SPECIFICATIONS & SPECIAL

### 技术规格及特点

#### FEATURES

- |   |                               |
|---|-------------------------------|
| 1. Material: SUS304; LID OPENING GASKET- PTFE                         | 1. 材料: SUS304; 人孔密封圈-聚四氟乙烯。   |
| 2. External Dimensions: 1,150×1,150×1,355mm                           | 2. 箱外尺寸: 1,150×1,150×1,355mm  |
| 3. Maximum Payload: 1,750KG   | 3. 最大载重: 1,750KG              |
| 4. Surface treatment: 2B (JIS)  | 4. 外表面处理: 2B (JIS)            |
| 5. Surface treatment: 2B (JIS); welding line with acid-washing.       | 5. 表面处理: 外表面 2B (JIS), 焊缝处酸洗。 |
| 6. Approvals: UN  | 6. 通过 UN 认证                   |
| 7. Reserving and transportation for hazard chemical, solid grain etc. | 7. 适于储存和运输危险化学品等固体颗粒。         |



		Dimensions	MM	FT - IN
External 箱 外	Length (长度)		1257	4' - 1 1/2"
	Width (宽度)		1105	3' - 7 1/2"
	Height (高度)		1905	6' - 3"
Internal 箱 内	Length (长度)		1213	3' - 11 3/4"
	Width (宽度)		1061	3' - 5 3/4"
	Height (高度)		1692	5' - 6 5/8"
Fork Pocket Height	叉 槽 高 度		140	5 1/2"
MANHOLE OPENING DIAMETER	人孔直径		567	1' - 10 3/8"
OUTLET DIAMETER	排料孔直径		50A	2"
Inside Cubic Capacity 容 积			CU.M	CU.FT
			2.082	73.57
Tare Weight (nominal)	自 重 (名义)		KG	LBS
			260	573.1
Stacking Capacity (in static)	允许堆码层数 (静载)	2 high		
Stacking Capacity (in transit)	允许堆码层数 (动载)	1 high		
<b>SPECIAL FEATURES 特点</b>				
1. Material: BODY- SUS304 JIS G 4305				
材料: 筒体 - SUS304 JIS G 4305				
2. Surface treatment: 2B (JIS), welding line with acid treatment				
表面处理: 2B (JIS) 焊缝处酸洗				
3. Approval of UN31AY				
通过 UN 认证				
4. Storing and transportation for Group II, III dangerous liquid goods				
适于包装和运输 II、III类危险品				

Interested and require more information? Please contact your local representative or email us at [info@sbhsolutions.com.au](mailto:info@sbhsolutions.com.au)